

A9408335

SHELL-TYPE CASES G 155, Vers. IV

Two-part plastic case with closed front and rear. Guide ridges and fastening pillars for mounting of PCBs in top and base.

Version

With battery compartment for 1 x 9 V flat battery (PP3) or 2 x 1.5 V mignon cells (AA)

Supply

1 top and base part, battery compartment lid, assembly kit



TECHNICAL DATA

Material	ABS (UL 94 HB)	Width	95 mm
Colour	off-white RAL 9002	Depth	158 mm
Standards	RoHS compliant, REACH compliant	Height	33 mm
		PCB length, base	119 mm
		PCB width, base	77 mm
		PCB length, top	149 mm
		PCB width, top	77 mm

Please take the dimensions from current parts. These are subject to material- and manufacturing-specific tolerances.

PURCHASING DATA

Weight/1 part	140 g
Customs tariff number (OKW product)	39269097
Country of manufacture	Germany

A9408335

SHELL-TYPE CASES G 155, Vers. IV

CUSTOMISING OPTIONS

What else do you need to create your own personal product? We can supply our enclosures and tuning knobs fully modified to suit your electronic components and design requirements. Please advise for anything else we can do for you.

Customising options for A9408335



Machining



Lacquering



Printing



Laser marking



Special material



EMC shielding




Installation / Assembly
of accessories

A9408335

SHELL-TYPE CASES G 155, Vers. IV

ACCESSORY "BATTERY"



A9160003
Plug-in contact, 1 x 9 V (PP3)



A9190014
Set of battery clips, 2 x AA
Steel
nickel-plated




A9250250
Battery spacer
PE foam
50x25x4mm

ACCESSORY "PROTECTION"



A9108120
Contact-strips V, O, G 155
Aluminium



A9108486
Sealing kit G 155

ACCESSORY "CARRYING"



A9100002
Ring eyelet
PA 6
volcano

ACCESSORY "SCREWS"



A0306031
Self-tapping screws 3 x 6 mm
(PZ1)

A9408335




SHELL-TYPE CASES G 155, Vers. IV

ACCESSORY



A9210290
Anti-slide feet 9.5 x 3.8 mm
transparent

Subject to technical modification without notice. © by OKW Gehäusesysteme, Buchen/Germany.



1:1

max. size of PCB: top part 77 x 149 mm, base part without battery compartment 77 x 119 mm (cutouts for pillars not taken into consideration)