

SHORT FORM CATALOG

EMC/EMI & Power Quality Filters and Components.



Table of Contents


Industries	4
Product Selection EMC/EMI	8
Product Selection PQ	9
DC Filters	10
Single-Phase Filters	11
IEC Inlet Filters and Power Entry Modules	12
Power Cords with Locking Systems	13
3-Phase Filters	14
3-Phase with Neutral Line Filters	15
Feedthrough Components	16
PCB Filters	17
EMC/EMI Chokes	18
Pulse Transformers	19
Active Harmonic Filters	20
3-Phase Line Reactors and LCL Filters	21
Passive Harmonic Filters	22
Output Filters and 3-Phase Load Reactors	23

Industries



Machinery & Robotics

Motor Drive,
Machinery,
Factory
Automation,
Robotics



Building Technology

HVAC, Elevators,
Lighting



Energy Management

Renewable
Energy, EV-
Charging, Energy
Storage, Smart
Infrastructure,
Power Supply,
UPS, Oil & Gas



Medical

Medical
Equipment,
Laboratory
and Analyser
Equipment



Data & Communication

Datacenter,
Networks

DC Filters



FN2200	■		■		
FN2210, FN2211	■		■		
FN2210HV, FN2211HV	■		■		
FN2220, FN2230, FN2240 NEW			■		

Single-Phase Filters



FN2010			■	■	
FN2020			■	■	
FN2030			■	■	
FN2060		■	■	■	
FN2070, FN2071	■	■	■	■	
FN2080	■	■	■	■	
FN2090, FN2091	■	■	■	■	
FN2410, FN2412	■	■	■		
FN2415	■				
FN2450	■	■	■	■	
FN2500, FN2520 NEW	■	■	■		
FN2560 NEW		■			
FN2580 NEW		■			
FN332			■	■	
FN343			■		
FN350	■				
FN352Z, FN353Z		■	■		■
FN700Z			■	■	■
LIS140C-1E NEW		■	■		

3-Phase Filters




FN3025, FN3026	■		■	■	
FN3100	■		■		
FN3120H	■		■		
FN3258	■	■	■		
FN3268	■	■	■	■	
FN3270, FN3271	■	■	■		
FN3287, FN3288	■	■	■	■	
FN3310, FN3311	■	■	■		
FN3310HV, FN3311HV	■	■	■		
FN3359	■		■		
FN3840 NEW	■	■			
FN351	■	■			



Machinery & Robotics

Motor Drive,
Machinery,
Factory
Automation,
Robotics



Building Technology

HVAC, Elevators,
Lighting



Energy Management

Renewable
Energy, EV-
Charging, Energy
Storage, Smart
Infrastructure,
Power Supply,
UPS, Oil & Gas



Medical

Medical
Equipment,
Laboratory
and Analyser
Equipment



Data & Communication

Datacenter,
Networks

3-Phase Filters with Neutral



FN3256H	■	■	■	■	
FN3280H	■	■	■		
FN354			■	■	
FN355			■	■	

IEC Inlet Filters and Power Entry Modules



FN2640, FN2660 NEW			■		■
FN9222			■	■	
FN9222E			■	■	
FN9226			■	■	
FN9233			■	■	
FN9233E			■	■	
FN9244			■	■	
FN9244E			■	■	
FN9246			■	■	
FN9255			■	■	
FN9255E				■	
FN9260			■	■	
FN9261			■	■	
FN9262			■	■	
FN9264			■	■	
FN9266			■	■	
FN9274 NEW				■	
FN9280			■	■	
FN9280E			■	■	
FN9290, FN9299			■	■	
FN280			■	■	
FN370, FN372, FN378, FN379			■	■	
FN380			■	■	
FN390, FN1390			■	■	
Power Cords with EMC-Filter IF13		■	■		■

EMC/EMI Chokes




ED Common Mode Chokes NEW		■			
EV/EH Common Mode Chokes		■	■	■	■
RB Common Mode Chokes	■	■	■	■	■
RC Common Mode Chokes	■	■	■	■	■
RD Common Mode Chokes	■	■	■	■	■
RI Saturation Chokes	■	■			
RN Common Mode Chokes	■	■	■	■	■
RS Differential Mode Chokes		■	■	■	■
RT Common Mode Chokes NEW	■	■	■	■	■
RV Common Mode Chokes NEW		■	■		

Industries



Machinery & Robotics
Motor Drive, Machinery, Factory Automation, Robotics



Building Technology
HVAC, Elevators, Lighting



Energy Management
Renewable Energy, EV-Charging, Energy Storage, Smart Infrastructure, Power Supply, UPS, Oil & Gas



Medical
Medical Equipment, Laboratory and Analyser Equipment



Data & Communication
Datacenter, Networks

PCB Filters



FN402			■	■	■
FN405			■	■	■
FN406		■	■	■	■
FN409		■	■		■
FN410		■	■		■

Feedthrough Capacitors & Filters



FN7510, FN7511, FN7512, FN7513, FN7514				■	■
FN7560, FN7561, FN7562, FN7563					■
FN7611, FN7612				■	■
FN7660, FN7661					■

Pulse Transformers



IT series, single secondary winding	■	■	■		
IT series, double secondary winding	■	■	■		


Accessories



IL13, 13 P, 19 Power Cords with Locking System		■	■	■	■
IL13P Angled IEC Lock C13		■	■	■	■
IL13P Rewireable IEC Locking Connector		■	■	■	■
IL13P Rewireable Angled Locking Connector		■	■	■	■



Machinery & Robotics
Motor Drive,
Machinery,
Factory
Automation,
Robotics



Building Technology
HVAC, Elevators,
Lighting



Energy Management
Renewable
Energy, EV-
Charging, Energy
Storage, Smart
Infrastructure,
Power Supply,
UPS, Oil & Gas



Medical
Medical
Equipment,
Laboratory
and Analyser
Equipment



Data & Communication
Datacenter,
Networks

Active Harmonic Filters



FN3530, FN3531, FN3540, FN3541	■	■	■	■	■
FN3532, FN3542	■	■	■	■	■
FN3545	■	■	■	■	■
SYNC300A, SYNC300X	■	■	■	■	■

Passive Harmonic Filters



FN3440, FN3442, FN3450, FN3452	■	■			
FN3441, FN3443, FN3451, FN3453	■	■			
FN3470, FN3472, FN3480, FN3482	■	■			
FN3471, FN3473, FN3481, FN3483	■	■			
FN3416, FN3418	■	■			
FN3416LV, FN3418LV	■	■			

Output Filters



FN5060, FN5060HV	■	■			
FN5420, FN5040HV, FN5020	■				
FN5030, FN530	■				

Reactors



RWK3044, RWK3062	■	■	■		
RWK305, RWK5420	■	■	■		

LCL Filters



FN6840	■		■		
--------	---	--	---	--	--

Product Selection EMC/EMI

EMC/EMI Filters & Components									
Single-Phase Filters					DC-Filters	3-Phase Filters			
PCB Filters	Feedthrough Components	Chassis Mount Filters			DC-Filters	3-Phase Filters		3-Phase Filters with Neutral	
≤10 A FN402 FN405 FN406 FN409 FN410	≤250 A Capacitors FN7510 FN7511 FN7512 FN7513 FN7514 FN7560 FN7561 FN7562 FN7563 Filters FN7611 FN7612 FN7660 FN7661	≤100 A Standard Performance FN2010 FN2020 FN2410 FN2412 FN2450 FN332 FN350	≤36 A High Performance FN2030 FN2060 FN2070 FN2071 FN2080 FN2415 FN2500 FN343	≤32 A Very High Performance FN2090 FN2091 FN2520 FN2560 FN2580 FN352Z FN353Z FN700Z	25 A–2300 A FN2200 FN2211 FN2210 FN2211HV FN2210HV EV-Charging Application FN2230 FN2231 FN2220 FN2221 FN2240 FN2241	≤300 A FN3025 FN3026 FN3100 FN3120H FN3258 FN3287 FN3288 FN3268 FN3840 FN351	25 A–2300 A FN3270 FN3271 FN3310 FN3311 FN3310HV FN3311HV FN3359	3 A–30 A FN354 FN355	8 A–600 A FN3256H FN3280H FN356
Page 17	Page 16	Page 11	Page 11	Page 11	Page 10	Page 14	Page 14	Page 15	Page 15

IEC Inlet Filters/Power Entry Modules PEM			
IEC Inlet Filters	PEM with Fuse or Switch	PEM with Fuse and Switch or Voltage Selector	Power Cords with Filters
≤20 A FN2640 FN2660 FN9222 FN9222E FN9226 FN9233 FN9233E FN9244 FN9244E FN9246 FN9255 FN9255E FN9274	≤10 A FN9260 FN9261 FN9262 FN9264 FN9266	≤10 A FN1390 FN9280 FN9280E FN9290 FN9299 FN280 FN370 FN372 FN378 FN379 FN380 FN390	≤10 A IF13
Page 12	Page 12	Page 12	Page 12

EMC/EMI Chokes				
Saturation Chokes	Differential Mode Chokes	Common Mode Chokes		
≤25 A RI Series	≤4 A RS Series	Single-Phase 0.2 A–10 A ED Series EV/EH Series RC Series RD Series RN Series RS Series 6 A–63 A RT Series RV Series	3-Phase 6 A–64 A RD Series RT Series	3-Phase with Neutral 6 A–64 A RD Series RV Series
Page 18	Page 18	Page 18	Page 18	Page 18

Product Selection PQ

Harmonic Filters		
Mitigation Requirement		
Active FN3530 FN3531 FN3540 FN3541 FN3532 FN3542 FN3545	Passive ≤250kW FN3440 FN3441 FN3442 FN3443 FN3450 FN3451 FN3452 FN3453 FN3416 FN3418 FN3416LV FN3418LV	Passive ≥250kW FN3470 FN3471 FN3472 FN3473 FN3480 FN3481 FN3482 FN3483
Page 20	Page 22	Page 22

3-Phase Reactors and LCL Filters			Output Filters	
Line Side		Load Side	Voltage Shape	
Line Reactors 4% ≤1000 A RWK3044 RWK3062	LCL Filters 25 A FN6840	Load Reactors 0.8% ≤1000 A RWK305 6% ≤1000 A RWK5420	dv/dt Filters ≤1200 A FN5060 FN5060HV	Sine Wave Filters ≤1320 A FN5420 FN5040HV FN530 FN5030
Page 21	Page 21	Page 23	Page 23	Page 23

DC Filters

DC filters are specifically optimized for applications with DC supply like EV charging, DC grids, energy storage and PV installations.

			Rated current [A]						Features			
			25	150	250	600	1000	2300	1-stage filter circuit	2-stage filter circuit	Low frequency attenuation	High frequency attenuation
			Attenuation Performance									
	Family	Max. Voltage	standard			high		very high				
	FN2200	1200 VDC	25			2300						
	FN2210 FN2211	1000 VDC				250		2300				
	FN2210HV FN2211HV	1500 VDC				250		2300				
	FN2220 FN2221	1000 VDC	150			600						
	FN2230 FN2231	500 VDC	150			600						
	FN2240 FN2241	1000 VDC	150			600						

Single-Phase Filters

Single-Phase filters for chassis or DIN-rail mounting are key for EMC compliance of low to medium power industrial applications. A broad selection of electrical and mechanical features allows a specific choice and deployment for countless applications.



	Family	Max. Voltage	Rated current [A]			Choice of connectors	Low frequency attenuation	High frequency attenuation	Earth line choke	Overvoltage protection	TEMPEST protection	DIN Rail Mounting	Multiple terminal choice
			standard	high	very high								
	FN2010	250 VAC/VDC	1	60									
	FN2020	250 VAC/VDC	1	60									
	FN2030	250 VAC/VDC	1	30									
	FN2060	250 VAC/VDC	1	30									
	FN2070	250 VAC/VDC	1	36									
	FN2071	250 VAC/VDC	1	16									
	FN2080	250 VAC/VDC	1	16									
	FN2090	250 VAC/VDC	1	30									
	FN2091	250 VAC/VDC	1	30									
	FN2410	250 VAC	8	100									
	FN2410H	520 VAC	8	45									
	FN2412	250 VAC	8	45									
	FN2412H	520 VAC	8	45									
	FN2415	250 VAC	6	20									
	FN2450	250 VAC	6	20									
	FN2500	277 VAC	10	32									
	FN2520	400 VDC	10	32									
	FN2560	300 VAC	1	8									
	FN2580	300 VDC	1	8									
	FN332	350 VAC	1	10									
	FN343	250 VAC	1	10									
	FN350	250 VAC	8	55									
	FN352Z	250 VAC	6	10									
	FN353Z	250 VAC	6	10									
	FN700Z	250 VAC	6	20									
	LIS140C-1E	230 VAC	1	40									

IEC Inlet Filters and Power Entry Modules

A powerful and compact combination of IEC connector, EMC/EMI filter, fuses, switch and voltage selector in one package.

Features

	Family	Max. Voltage	Rated current [A]					Fuse(s)	Switch (2-pole)	Voltage selector	Snap-in version	Extra wide mounting	Earth line choke	PCB mounting	Multiple terminal choice
			1	2	6	10	15								
			Attenuation Performance												
			standard	high	very high										
	FN9222	250 VAC	1					20							
	FN9222E	250 VAC	1					15							
	FN9226	250 VAC	1					10							
	FN9233	250 VAC	1					15							
	FN9233E	250 VAC	1					15							
	FN9244	250 VAC	1					15							
	FN9244E	250 VAC	1					15							
	FN9246	250 VAC	1					20							
	FN9255	250 VAC		2					20						
	FN9255E	250 VAC		2					15						
	FN9260 FN9261	250 VAC	1					10							
	FN9262 FN9266	250 VAC	1					10							
	FN9264	250 VAC	1					10							
	FN9274	250 VAC	1					15							
	FN9280	250 VAC	1					10							
	FN9280E	250 VAC	1					10							
	FN9290 FN9299	250 VAC	1					10							
	FN2640	250 VAC						10							
	FN2660	250 VAC						10							
	FN280, FN281, FN282, FN283 FN284, FN285, FN286	250 VAC	1					10							
	FN370, FN372, FN378, FN379	250 VAC		2	6										
	FN380, FN382, FN385B FN388, FN389	250 VAC		2	6										
	FN390 (6 A) FN1390 (10 A)	250 VAC	1					10							
	IF13	250 VAC						10							

Power Cords with Locking Systems

Guarding against accidental disconnection of all electrical appliances with an IEC inlet, no exchange or modification of the IEC inlet or IEC inlet filter is needed. An easy retrofit for all electronic equipment and devices is possible.





Family	Max. Voltage	■ standard length × on request								C14 line side plug IEC C14 male, straight C20 line side plug IEC C20 male, straight EU1 line side plug CEE7/VII right angled US1 line side plug NEMA5-15 straight US2 line side plug NEMA5-15 straight hospital grade UK1 line side plug BS1363, right angled, fused 5 A CH1 line side plug SEV1011 straight JP1 line side plug JIS8303 straight							
		6 ft	2 m	3 m	9 ft	12 ft	5 m	10 m									
 IL13	250 VAC	■	■	×	■	■	×	×	■			■	■	■	■	■	
 IL19	250 VAC		■								■	■	■		■		
 IL13P	250 VAC	Rewireable Connectors with Locking System															

3-Phase Filters

EMC/EMI filter solutions for industrial applications like motor drives and machine tools. Furthermore, these types of filters are also suitable for large uninterruptible power supplies, medical equipment, wind turbine power stations and a vast array of other 3-phase power electronics.

			Features									
	Family	Max. Voltage	Rated current [A]			Multi-stage filter circuit	Safety connector blocks	Low leakage current	Versions for IT networks	Busbar connection	Optional protective covers	DIN-rail mounting option
			7	50	180							
			Attenuation Performance									
			standard	high	very high							
	FN3025	520 VAC	10	50			■	■				
	FN3026	520 VAC	10	50			■	■				■
	FN3100	520 VAC		35	300		■					
	FN3120	520 VAC		25	230		■					
	FN3258 FN3258H	480 VAC 520 VAC	7	180			■					
	FN3268	520 VAC	7	180			■	■				
	FN3270 FN3271	520 VAC	10		1000		■			■	■	
	FN3287	530 VAC	10	230			■	■				
	FN3288 FN3288IT	530 VAC	10	230			■	■	■	■		
	FN3288HV FN3288HVIT	760 VAC	10	230			■	■		■		
	FN3310 FN3311	520 VAC			250	2300				■	■	■
	FN3310HV FN3311HV	760 VAC			250	2300				■	■	■
	FN3359 FN3359HV	520 VAC 760 VAC		150		2500	■			■	■	■
	FN3840	530 VAC		25	380			■			■	
	FN351 FN351H	440 VAC 520 VAC	8	280				■				

Feedthrough Components

Interference suppression up into the GHz range for high-tech applications such as IT, telecom, server and networking equipment.

									Features					
			Rated current [A]											
			Capacitance [nF]											
			2.2	100	220	470	1000	4700	AC capacitors	DC capacitors	AC filters	DC filters	Y2 capacitor class	Y4 capacitor class
Feedthrough Capacitors	Max. Voltage													
	FN7510	300 VAC 250 VAC (UL)	2.2	47	10	100			■				■	
	FN7511	300 VAC 250 VAC (UL)	4.7	220	10	200			■				■	
	FN7512	300 VAC 250 VAC (UL)	33	100	16	63			■				■	
	FN7513	300 VAC 250 VAC (UL)		100	16				■				■	
	FN7514	300 VAC 250 VAC (UL)		100	32				■				■	
	FN7560	130 VDC 130 VAC	10	100	10	200			■	■				■
	FN7561	130 VDC 130 VAC	47	470	63	200			■	■				■
	FN7562	130 VDC 130 VAC		100	16	200	1000		■	■				■
	FN7563	130 VDC 130 VAC		470	16	200	4700		■	■				■

			Rated current [A]											
			Attenuation Performance											
			standard	high	very high									
Feedthrough Filters	Max. Voltage													
	FN7611	300 VAC 250 VAC (UL)	10	63						■			■	
	FN7612	300 VAC 250 VAC (UL)	10	63						■			■	
	FN7660	130 VDC 130 VAC	10	200						■	■			■
	FN7661	130 VDC 130 VAC	10	200						■	■			■

PCB Filters

Very compact EMI suppression components can directly be mounted on printed circuit boards of low-power office, medical, telecom and IT equipment, DC/DC converters and power supplies etc. Ideal low cost solution for manufacturers who already planned for EMC compliance throughout the equipment design process.



			Rated current [A]									
			0.536.58.41013									
			Attenuation Performance									
			standardhighvery high									
Family	Max. Voltage								For DC applications	With metal case	Low profile	Small footprint
	FN402	250 VAC	0.56.5									
	FN405	250 VAC	0.510									
	FN406	250 VAC	0.58.4									
	FN409	75 VDC	313									
	FN410	250 VAC	0.56									

EMC/EMI Chokes

An extensive selection of discrete EMC/EMI chokes with various inductance and current ratings allows optimized circuitry for EMC compliance to be designed easily and economically.

Features

			Rated current [A]														
			0.2	0.7	3	6	16	50	64	Common mode choke	DC application	Single phase	3-phase	3-phase with neutral	Differential mode choke	Saturation choke	High differential mode inductance
			Inductance value [mH] up to:														
			0	20	40	60	80	100									
NEW 	ED series	300 VAC	0.2	2													
					40												
	EV/EH series	250 VAC	0.3	5													
							90										
	RB series	600 VAC 1000 VDC					16	50									
			3														
	RC series	250 VAC 1000 VDC	0.25	0.7													
					47												
	RD 5000 series	600 VAC 850 VDC					6	16									
			10														
	RD 6000 series	600 VAC 850 VDC					6	16									
			15														
	RD 7000 series	600 VAC 850 VDC					6	36									
			25														
	RD 8000 series	600 VAC 850 VDC					16	64									
			12														
	RI series	250 VAC		1.5			25										
	RN series	300 VAC 300 VDC	0.3	10													
							100										
	RS series	250 VAC	0.3	4													
					3.6												
NEW 	RT series	600 VAC 425 VDC					6	63									
			10														
NEW 	RV series	530 VAC 1000 VDC					16	50									
			16														

Pulse Transformers

They provide a proper galvanic separation between gate drive circuitry and high voltage path in IGBT, thyristor, triac, power MOSFET and DC/DC converter circuits.






			Features											
Family	Nom. Voltage		Ignition current [A] up to:						Voltage-time area [Vμs] up to:					
			0	0.6	1.2	1.8	2.4	3.0	0	1000	2000	3000	4000	5000
	IT155 IT237	500 VAC	0.25											
				1100										
	IT245, IT255, IT258	750 VAC	1											
				500										
	IT239	1000 VAC	0.25											
				350										
	IT370	1000 VAC	1											
					4000									
	IT364	3000 VAC	3											
					5000									
	IT213	380 VAC	0.25											
				450										
	IT312 IT313	380 VAC	1											
					1200									
	IT143, IT233, IT242, IT243, IT253	500 VAC	0.25											
				800										
	IT245 IT248	750 VAC	0.25											
				350										
	IT249	500 VAC	0.25											
				350										
	IT260	500 VAC	0.1											
				200										
	IT314	380 VAC	1											
				500										
	IT234, IT244, IT154	500 VAC	0.25											
				600										

3-Phase Line Reactors and LCL Filters

Line side harmonic mitigation solutions for industrial applications like motor drives and Active Front End/Active Infeed Converters. 3-Phase Line Reactors offer a first stage of mitigation with possibility to combine with other filtering solutions like an Active Harmonic Filter. LCL Filters protect the grid from disturbances induced during energy regeneration from the Active Front End.



	Family	Nom. Voltage	Rated mitigation current [A]																
			0	200	400	600	800	1000	<1000										
	RWK3044	380–480 VAC	2 1000							■	■	■	■	■	■	■	■	■	■
	RWK3062	500–690 VAC	1.5 870							■	■	■	■	■	■	■	■	■	■
	FN6840	380–480 VAC	25							■	■			■	■	■	■	■	



Headquarters, Global Innovation and Development

Switzerland

Schaffner Group

Industrie Nord
Nordstrasse 11 e
4542 Luterbach
P + 41 32 681 66 26
info@schaffner.com

Sales and Application Centers

China

Schaffner EMC Ltd. Shanghai

T20 - 3 C No 565 Chuangye Road
Pudong district 201201
P + 86 21 38 139 500
cschina@schaffner.com

Finland

Schaffner Oy

Sauvonrinne 19 H
08500 Lohja
P + 358 50 468 72 84
finlandsales@schaffner.com

France

Schaffner EMC S.A.S.

16 - 20 Rue Louis Rameau
95875 Bezons
P + 33 1 34 34 30 60
francesales@schaffner.com

Germany

Schaffner Deutschland GmbH

Schoemperlenstrasse 12 B
76185 Karlsruhe
P + 49 721 56 910
germanysales@schaffner.com

India

Schaffner India Pvt. Ltd

Regus World Trade Centre
WtC 22nd Floor Unit No 2238
Brigade Gateway Campus 26 / 1
Dr. Rajkumar Road
Malleshwaram (W)
560055 Bangalore
P + 91 80 679 35 355
indiasales@schaffner.com

Italy

Schaffner EMC S.r.l.

Via Ticino 30
20900 Monza (MB)
P + 39 039 21 41 070
italysales@schaffner.com

Japan

Schaffner EMC K.K.

Taiju - Seimei Sangenjaya Bldg.
1 - 32 - 12 Kamiuma Setagaya-ku
154 - 0011 Tokyo
P + 81 3 57 12 36 50
japansales@schaffner.com

Singapore

Schaffner EMC Pte Ltd.

05 - 09 Kg Ubi
Ind. Estate 408705
P + 65 63 77 32 83
singaporesales@schaffner.com

Spain

Schaffner EMC España

Calle Caléndula 93 Miniparc III
Edificio El Soto de Moraleja
Alcobendas 28109 Madrid
P + 34 917 912 900
spainsales@schaffner.com

Sweden

Schaffner EMC AB

Östermalmstorg 1
114 42 Stockholm
P + 46 8 50 50 2425
swedensales@schaffner.com

Switzerland

Schaffner EMV AG

Industrie Nord
Nordstrasse 11 e
4542 Luterbach
P + 41 32 681 66 88
P + 41 32 681 66 26
switzerlandsales@schaffner.com

Taiwan

Schaffner EMV Ltd.

20 Floor - 2 No 97 Section 1
XinTai 5th Road
22175 XiZhi District
New Taipei City 22175
P + 886 2 2697 55 00
taiwansales@schaffner.com

Thailand

Schaffner EMC Co. Ltd.

Northern Region Industrial
Estate 67 Moo 4 Tambon
Ban Klang Amphur Muang
P.O. Box 14 51000 Lamphun
P + 66 53 58 11 04
thailandsales@schaffner.com

United Kingdom

Schaffner Ltd.

1 Oakmede Place Binfield
RG42 4JF Berkshire
P + 44 118 977 00 70
uksales@schaffner.com

USA

Schaffner EMC Inc.

52 Mayfield Avenue
Edison New Jersey
P + 1 732 225 95 33
usasales@schaffner.com

To find your local partner within
Schaffner's global network, please visit
[schaffner.com](https://www.schaffner.com)


The information contained within this document and the functions offered are solely intended to provide information about products available for purchase from Schaffner group companies ("Schaffner") and do not constitute an offer for purchase or sale or a recommendation or advice. The content of this document has been carefully prepared and reviewed and all reasonable efforts have been made to ensure the accuracy of the information. However, Schaffner does not warrant the accuracy and does not assume any liability whatsoever for any errors or inaccuracies of this document and the consequences thereof. Schaffner accepts no responsibility or liability for any losses or damages of any kind arising out of the use of this document or any of its related functions. Further, Schaffner cannot be held responsible for any errors or unexpected unfulfillment of shipments. Schaffner reserves the right to make changes to this document, the products, the published specifications and any other functions at any time without notice. Product suitability for any area of application must ultimately be determined by the customer. In all cases, products must never be operated outside their published specifications. Schaffner does not warrant, represent or guarantee the availability of any or all published products. The latest publications and product specification sheets as well as the current Schaffner general terms and conditions and data protection policy apply; these documents and the complete legal disclaimer can be downloaded from the Schaffner website. In order to improve readability, the masculine form is mainly used for people and personal nouns in this document. All references to persons apply equally to all genders. The abbreviated language form has only editorial reasons and does not imply any valuation.

All intellectual property rights, such as trademarks, tradenames, designs and copyrights, are reserved and are exclusively owned by Schaffner Holding AG.

This document may exist also in other languages. This version is valid and binding.

This disclaimer shall be governed by substantive Swiss law and resulting disputes shall be settled by the courts at the place of business of Schaffner Holding AG.

© 2022 Schaffner Holding AG

An abstract graphic consisting of several thin, curved lines that flow from the left side of the page towards the right, creating a sense of movement and energy. The lines are a lighter shade of red than the background.

Schaffner Group
Nordstrasse 11e
4542 Luterbach
Switzerland
P + 41 32 681 66 26
info@schaffner.com

[schaffner.com](https://www.schaffner.com)

schaffner
MORE POWER TO YOU